



CAMERA



VANDAL PROOF DAY & NIGHT DOME CAMERA

ADV 228



FEATURES

- Hi-impact reinforced polycarbonate Armor Dome withstand a blow 10-pound sledgehammer.
- Reinforced polycarbonate with special coating on surface
- Max. Load 500 kg deformation without crack
- Die-Casting Base: Ultra hard grade aluminum with painting finish

SPECIFICATION

Model	ADV 228
Image Sensor	1/3" Sony Super HAD CCD Color Sensor
Scanning System	2:1 Interlace
	30 Frames (NTSC) 25 Frames (PAL)
	525 Lines Interlaced (NTSC) 625 Lines Interlaced (PAL)
Effective Pixels	768 (H) x 494 (V) (NTSC) 752 (H) x 582 (V) (PAL)
Resolution	580 TV Lines
Minimum Illumination	0.01 Lux / F 1.2
S/N Ratio	More Than 48dB (AGC Off)
Video Output	1.0 Vp-p composite, 75ohm
Gamma Ratio	0.45
White Balance	Auto
Back Light Compensation	Auto
Auto Gain Control	Auto
Iris Mode	AES
Synchronization	Internal
Electronic Shutter	1/60 to 1/100,000 sec (NTSC) 1/50 to 1/100,000 sec (PAL)
Lens	f = 3.6mm / F1.2
Vandal Proof Rating	IP 66
Power Source / Power Consumption	DC12V ± 10% / 140mA
Operating Temperature	- 20°C to + 50°C
Weight / Dimension	Approx. 450g / Ø 142.0 x 84.0H mm

Design and specifications are subject to change without prior notice

