

# IR DOME CAMERA - Metal Case

## ADV 3036DM



### SPECIFICATION

Model	ADV 3036DM
Image Sensor	1/3" Sony Super HAD Color CCD Sensor
Scanning System	2:1 Interlace
	30 Frames (NTSC)    25 Frames (PAL)
Effective Pixels	525 Lines Interlaced (NTSC)    625 Lines Interlaced (PAL)
Resolution	510 (H) x 492 (V) (NTSC)    500 (H) x 582 (V) (PAL)
Minimum Illumination	480 TV Lines
S/N Ratio	0.5 Lux / F 1.2    0 Lux When IR On
Video Output	More Than 48dB (AGC Off)
Gamma Ratio	1.0 Vp-p composite, 75ohm
White Balance	0.45
Back Light Compensation	Auto
Auto Gain Control	Auto
Iris Mode	Auto
Synchronization	AES
Electronic Shutter	Internal
Lens	1/60 to 1/10,000 sec (NTSC)    1/50 to 1/10,000 sec (PAL)
Power Source	f = 3.6mm / F1.2
Power Consumption	DC12V ± 10%
LED / Effective Length	110mA, 320mA When IR on
Operating Temperature	36 Units IR LED / 30M
Weight / Dimension / Case	- 20°C to + 50°C
	Approx. 320g / Ø 121.8 x 85.0 (H) mm / Metal Case

*Design and specifications are subject to change without prior notice*