



CAMERA



PIR CAMERA

ADV 308



SPECIFICATION

Model	ADV 308
Image Sensor	1/3" Sony Color CCD Sensor
	2:1 Interlace
Scanning System	30 Frames (NTSC) 25 Frames (PAL)
	525 Lines Interlaced (NTSC) 625 Lines Interlaced (PAL)
Effective Pixels	512 (H) x 492 (V) (NTSC) 510 (H) x 582 (V) (PAL)
Resolution	480 TV Lines
Minimum Illumination	0.01 Lux / F 1.2
S/N Ratio	More Than 48dB (AGC Off)
Video Output	1.0 Vp-p composite, 75ohm
Gamma Ratio	0.45
White Balance	Auto
Back Light Compensation	Auto
Auto Gain Control	Auto
Iris Mode	AES
Synchronization	Internal
Electronic Shutter	1/60 to 1/10,000 sec (NTSC) 1/50 to 1/10,000 sec (PAL)
Lens	f = 3.6mm / F 1.2
Power Source	DC12V ± 10%
Power Consumption	140mA
Operating Temperature	- 10°C to + 50°C
Weight / Dimension	Approx. 120g / 47.0 (D) x 70.0 (W) x 119.0 (H) mm

Design and specifications are subject to change without prior notice

