



CAMERA



PIR CAMERA

AVC 816



SPECIFICATION

Model	AVC 816
Image Sensor	1/3" Sony Color CCD Sensor
Scanning System	2:1 Interlace
	30 Frames (NTSC) 25 Frames (PAL)
Effective Pixels	525 Lines Interlaced (NTSC) 625 Lines Interlaced (PAL)
Resolution	512 (H) x 492 (V) (NTSC) 512 (H) x 582 (V) (PAL)
Minimum Illumination	420 TV Lines
S/N Ratio	0.5 Lux / F 2.0
Video Output	More Than 48dB (AGC Off)
Gamma Ratio	1.0 Vp-p composite, 75ohm
White Balance	0.45
Auto Gain Control	Auto
Iris Mode	Auto
Synchronization	AES
Electronic Shutter	Internal
Lens	1/60 to 1/10,000 sec (NTSC) 1/50 to 1/10,000 sec (PAL)
Microphone	f = 3.6mm / F 2.0
Power Source	Yes
Power Consumption	DC12V ± 10%
Operating Temperature	100mA
Weight / Dimension	- 10°C to + 50°C
	Approx. 265g / 49.0 (L) x 70.0 (W) x 110.0 (H) mm

Design and specifications are subject to change without prior notice

AV TECH