



EagleEyes for Mobile Surveillance

Official Website : www.eagleeyescctv.com

: www.eagleeyescctv.com/video


: www.eagleeyescctv.com/facebook


AVM302A 1.3 MP IP Camera

FEATURES

- I Easy network setup with your iPhone / iPad
- I 1.3 Megapixel with HDTV 720p quality, allowing users to notice minor details more easily
- I ONVIF standard supported to simplify system integration
- I External alarm I/O device connection
- I Micro SD card support for video storage
- I POE (Power-over-Ethernet) support to eliminate the use of power cables and reduce installation costs
- I Microphone built-in for audio recording
- I Remote Surveillance
 - -- Fully compatibility on iPhone & iPad, and Internet Explorer on Windows operating system

DIMENSION (Tolerance: ± 5mm)











EagleEyes for Mobile Surveillance

Official Website : www.eagleeyescctv.com

Video Demo : www.eagleeyescctv.com/video Facebook : www.eagleeyescctv.com/facebook

SPECIFICATIONS

■ Network	
Network Compression	H.264 / MPEG4 / MJPEG
Multiple Video Streaming	
(Encode Modes, IPS, Resolution)	3 (H.264, MJPEG, MPEG4)
LAN Port	YES
LAN Speed	10/100 Based-T Ethernet
· · · · · · · · · · · · · · · · · · ·	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP,
Supported Protocols	ICMP, SMTP, FTP, HTTP, RTP, RTSP, UPnP
ONVIF Compatible	YES
Frame Rate	NTSC: 30, PAL: 25
Number of Online Users	10
Security	(1) Multiple user access levels with password
	(2) IP address filtering
	(3) Digest authentication
	(1) Internet Explorer on Windows operating system
Remote Access	(2) EagleEyes on iPhone, iPad & Android mobile devices
Camera	
Image Sensor	1/4" SONY CMOS image sensor
Video Resolution	SXGA, 720P, VGA, QVGA
Min Illumination	0.1 Lux / F1.5
Shutter Speed	1/2 to 1/10,000 sec
S/N Ratio	More than 48dB (AGC off)
Lens	f3.8mm / F1.5
Viewing Angle	62.7° (Diagonal) / 53.7° (Horizontal) / 34.1° (Vertical)
White Balance	ATW
AGC	Auto
IRIS Mode	AES
PIR Sensor	Detection Range 76° wide angle with up to 6m long distance
	at 2m height (under 30°C)
Micro SD Card Slot	YES
External Alarm I/O	YES
Microphone	YES
Power Source (±10%)	12V / 1A
Current Consumption	0.25A
Operating Temperature	0°C~40°C
■ Others	
Mobile Surveillance	iPad / iPhone / Android mobile device
POE (Power-over-Ethernet)	YES (IEEE 802.3af)
RTC (real-time clock)	YES
Motion Detection	YES
Digital Pan / Tilt / Zoom	YES
Event Notification	FTP / Email
	Intel core i3 or higher, or equivalent AMD
	GB RAM
Minimum Web	AGP graphics card, Direct Draw, 32MB RAM
Browsing Requirements	 Windows 7, Vista & XP, DirectX 9.0 or later
	Internet Explorer 7.x or later

* The specifications are subject to change without notice.