



EagleEyes for Mobile Surveillance

Official Website : www.eagleeyescctv.com Video Demo : www.eagleeyescctv.com/video

AVM357A Megapixel IR Network Camera

FEATURES

- Easy network setup with your iPhone / iPad
- **POE (Power-over-Ethernet)** support to eliminate the use of power cables and reduce installation costs
- **ONVIF** standard supported to simplify system integration
- External alarm I/O device connection
- IR LED built-in for night surveillance with effective range up to 20 meters
- Remote Surveillance

-- Fully compatibility on iPhone & iPad, and Internet Explorer® on Windows® operating system

SPECIFICATIONS

Network	
Network Compression	H.264 / MPEG4 / MJPEG
Multiple Video Streaming (Encode Modes, IPS, Resolution)	3 (H.264, MJPEG, MPEG4)
LAN Port	YES
LAN Speed	10/100 Based-T Ethernet
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP, RTCP,IPv4, Bonjour, UPnP, DNS,UDP,IGMP, QoS
ONVIF Compatible	YES
Frame Rate	NTSC:30, PAL:25
Number of Online Users	10
Security	 (1) Multiple user access levels with password (2) IP address filtering (3) HTTPS (4) Digest authentication
Remote Access	(1) Internet Explorer on Windows operating system(2) EagleEyes on iPhone, iPad & Android mobile devices
Camera	
Image Sensor	1/4" SONY HR image sensor
Video Resolution	SXGA, 720P, VGA, QVGA
Min Illumination	0.1 Lux / F1.5, 0 Lux (LED ON)
Shutter Speed	1 / 2 to 1 / 10,000 sec.
S/N Ratio	More than 48dB (AGC off)









EagleEyes for Mobile Surveillance

Official Website : www.eagleeyescctv.com Video Demo : www.eagleeyescctv.com/video Technical Support : support@eagleeyescctv.com

SPECIFICATIONS (Continued)

Camera		
Lens	f3.8mm / F1.5	
Viewing Angle	62.7°(Diagonal)	
IR LED	35 Uints	
IR Effective Range	Up to 20 meters	
IR Shift	YES	
White Balance	ATW	
AGC	Auto	
IRIS Mode	AES	
POE	YES (IEEE 802.3af)	
Memory Storage	10MB (Built-in)	
External Alarm I/O	YES	
Power Source (±10%)	12V / 1A	
Operating Temperature	-20 °C ~40°C	
■ Others		
Mobile Surveillance	iPad / iPhone / Android mobile device	
Motion Detection	YES	
Event Notification	FTP / Email	
RTC (real-time clock)	YES	
Digital Pan / Tilt / Zoom	YES	
Minimum Web Browsing Requirements	 Pentium 4 CPU 1.3 GHz or higher, or equivalent AMD 256 MB RAM AGP graphics card, Direct Draw, 32MB RAM Windows 7, Vista & XP, DirectX 9.0 or later Internet Explorer 7.x or later 	

*The specifications are subject to change without notice ** Dimensional tolerance: (± 5mm)

DIMENSIONS (mm)

