KPC137D



24LEDs IR Camera

FEATURES

- (1) Day and night features for 24-hour surveillance
- (2) Standard horizontal resolution and high quality picture
- (3) Minimum illumination of 0.3Lux / F2.0, 0 Lux (IR ON)
- (4) IR LED effective range reaches up to 15 meters
- (5) IP 67 standard approved case

SPECIFICATIONS*

| MODEL | KPC137D | | |
|----------------------------|---|--|--|
| Pick up Element | 1/3" Color CCD image sensor | | |
| Number of Pixel | 512(H) x 492(V) <ntsc> / 512(H) x 582(V) <pal></pal></ntsc> | | |
| Resolution | Standard | | |
| Min. Illumination | 0.3Lux / F2.0, 0Lux (15 meter IR ON) | | |
| IR LED | 24 units | | |
| Effective Range | Up to 15 Meters | | |
| S/N Ratio | More than 48dB (AGC off) | | |
| Electronic Shutter | 1/60 (1/50) to 1/100,000 sec. | | |
| Lens | f3.6mm / F2.0 | | |
| Lens Angle | 92.6° | | |
| IRIS Mode | AES | | |
| Gain Control | Auto | | |
| White Balance | ATW | | |
| IP Rating | IP 67 | | |
| Video Output | 1.0 Vp-p composite, 75Ω | | |
| Power Source (±10%) | DC12V | | |
| Current Consumption (±10%) | 90mA (IR OFF), 330mA (IR ON) | | |
| Dimension (mm)** | 100 (L) x 65 (W) x 63.8 (H) | | |

^{*} The specifications are subject to change without notice.

^{**} Dimensional Tolerance: ± 5mm