



CAMERA



KOREA
WEATHER PROOF IR CAMERA

OD 3054



SPECIFICATION

Model	OD 3054
Image Sensor	1/3" Sony Super HAD Color CCD Sensor
Scanning System	2:1 Interlace 30 Frames (NTSC) 25 Frames (PAL)
Effective Pixels	525 Lines Interlaced (NTSC) 625 Lines Interlaced (PAL)
Resolution	510 (H) x 492 (V) (NTSC) 500 (H) x 582 (V) (PAL)
Minimum Illumination	480 TV Lines 0.5 Lux / F 1.2 0 Lux When IR On
S/N Ratio	More Than 48dB (AGC Off)
Video Output	1.0 Vp-p composite, 75ohm
Gamma Ratio	0.45
White Balance	Auto
Back Light Compensation	Auto
Auto Gain Control	Auto
Iris Mode	AES
Synchronization	Internal
Electronic Shutter	1/60 to 1/10,000 sec (NTSC) 1/50 to 1/10,000 sec (PAL)
Lens	f = 6.0mm / F1.2
Power Source	DC12V ± 10%
Power Consumption	110mA, 650mA When IR on
LED / Effective Length	54 Units IR LED / 50M
Weather Resistance	IP 68
Operating Temperature	- 10°C to + 60°C
Weight / Dimension	Approx. 320g / Ø 70.0 x 110 (H) mm

Design and specifications are subject to change without prior notice

