



Network

Bullet

QNO-7012R

4MP IR Bullet Camera



Key Features

- Maximum 4MP resolution
- Color : 0.15Lux (F2.0, 1/30sec) B/W : 0Lux (IR LED On)
- 2.8mm fixed focal
- H.265, H.264, MJPEG codec supported, Multiple streaming
- Motion detection, Tampering, Defocus detection
- Hallway view (90°/270°), LDC support
- Micro SD/SDHC/SDXC memory slot (128GB)
- IR viewable length 20m (65.62ft)
- IP66, IK10, PoE, 12VDC

QNO-7012R

4MP IR Bullet Camera



Specifications

Video

| | | |
|-------------------------|---|------------------------|
| Imaging Device | Size | 1/3" |
| | Type | CMOS |
| Resolution | 2560x1440, 1920x1080, 1280x960, 1280x720, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240 | |
| Max. Framerate | H.265/H.264 | 30fps/25fps(60Hz/50Hz) |
| | MJPEG | 15fps(@4MP Max. 2fps) |
| Min. Illumination (Lux) | Color(1/30sec, 30IRE) | 0.15 |
| | BW(1/30sec, 30IRE) | 0.015 |
| Video Out | CVBS: 1.0 Vp-p / 75Ω composite for installation | |

Lens

| | | |
|-------------------------------|------------|------|
| Focal Length (mm) | 2.8 | |
| Max Aperture Ratio (F number) | Wide | 2.0 |
| Angular Field of View | Horizontal | 108° |
| | Vertical | 60° |
| | Diagonal | 122° |
| Focus Control | Fixed | |

Pan / Tilt / Rotate

| | | |
|---------------------------|--------|---------|
| Pan / Tilt / Rotate Range | Pan | 0°~360° |
| | Tilt | 0°~100° |
| | Rotate | 0°~360° |

Operational

| | | |
|-------------------------|-----------------|------------------------|
| Day & Night | Auto(ICR) | |
| Backlight Compensation | BLC, WDR, SSSDR | |
| Wide Dynamic Range (dB) | 120 | |
| Digital Noise Reduction | SSNR | |
| Motion Detection | Quantity | 4ea |
| | Shape | 8point Polygonal zones |

Operational

| | | |
|--|-------------|--|
| Privacy Masking | Quantity | 6ea |
| | Shape | Rectangular zones |
| Gain Control | | Low, Middle, High |
| White Balance | | ATW, AWC, Manual, Indoor, Outdoor |
| LDC | | Support |
| Electronic Shutter | Mode | Minimum, Maximum, Anti flicker |
| | Speed Range | 1/5~1/12,000sec |
| Video Rotation | | Flip, Mirror, Hallway view(90°/270°) |
| Alarm Interface | In/Out | Input 1ea, Output 1ea |
| Alarm Triggers | | Analytics, Network disconnect, Alarm input |
| Alarm Events When Alarm Trigger Occurred | | File upload(image): e-mail/FTP, Notification: e-mail, Recording: SD/SDHC/SDXC or NAS recording at event triggers,Alarm output, Handover: PTZ preset |
| Audio In | | Selectable(mic in/line in) |
| Light Type | | IR LED |
| Light Viewable Length | IR | 20m(65.62ft) |
| IR Wavelength | | 850nm |

Analytics

| | | |
|------------------|--------|---|
| Analytics Events | Normal | Defocus detection, Motion detection, Tampering, Virtual area(Intrusion/Enter/Exit), Virtual line(Crossing, Direction) |
|------------------|--------|---|

Network

| | | |
|-----------------------------------|--------------------|---|
| Ethernet | | RJ-45(10/100BASE-T) |
| Video Compression | | H.265/H.264: Main/High, MJPEG |
| Audio Compression | | G.711 u-law /G.726 selectable, G.726(ADPCM) 8kHz, G.711 8kHz, G.726: 16kbps, 24kbps, 32kbps, 40kbps |
| Smart Codec | | Manual, WiseStream II |
| Bitrate Control | | H.265/H.264: CBR or VBR, MJPEG: VBR |
| Streaming | Unicast | Up to 6 users |
| | Multicast | Support |
| | Multiple Streaming | Up to 3 profiles |
| Protocol | | IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP(TCP, UDP Unicast), PPPoE, PIM-SM |
| Application Programming Interface | ONVIF | S, G, T |
| | Others | SUNAPI(HTTP API) |
| Direct Cloud Connection | | Optional (needs gateway) |

Security

| | |
|------------------------|---|
| OS / Firmware Protect | Encrypted firmware |
| User authentication | Digest authentication, Prevent brute-force attack |
| Network authentication | IEEE 802.1X(EAP-TLS, EAP-LEAP, EAP-PEAP, MSCHAPv2) |
| Secure Communication | HTTPS, WSS(WebSocket Secure), SRTP |
| Access Control | IP-based access control |
| Data Protect | Encryption credentials, Encrypt compress for live recording file export |
| Audit | Access / System / Event Log management |
| Device ID | Device certificate(Hanwha Vision Root CA) |
| Secure Storage | SDcard partition encrypt(AES-256) |

General

| | | |
|--------------|--------------------|--------------------|
| Memory | RAM | 512MB |
| | Flash | 256MB |
| Edge Storage | Micro SD/SDHC/SDXC | Max. 128GB x 1slot |

Environmental & Electrical

| | | |
|---------------------|-------------|--|
| Operating Condition | Temperature | -40°C~+55°C(-40°F~+131°F) |
| | Humidity | 0~95% RH(non-condensing) |
| | Others | Start up should be done at above -30°C |
| Storage Condition | Temperature | -40°C~+60°C(-40°F~+140°F) |
| | Humidity | 0~95% RH(non-condensing) |
| Input Voltage | | PoE(IEEE802.3af, Class3), 12VDC |
| Power Consumption | PoE | Max. 10.7W, typical 8W |
| | 12VDC | Max. 9.1W, typical 6.8W |

Mechanical

| | |
|---------------------|----------------------------|
| Color | Dark grey |
| Material | Aluminum |
| Product Dimensions | ø70.0x246.0mm(2.76x9.69") |
| Product Weight | 700g(1.54lb) |
| Compatible Gang Box | Single, Double, 4" Octagon |

Certifications & Standards

| | |
|-------------|--|
| EMC | FCC 47 CFR 15 Subpart B Class A, ICES-3(A)/NMB-3(A), CE/UKCA - EN55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, VCCI CISPR 32 Class A, RCM AS-NZS CISPR 32 Class A, KS C 9832 Class A, KS C 9835 |
| Safety | UL 60950-1, CAN/CSA C22.2 NO. 60950-1, IEC 62471 |
| Environment | IEC/EN 63000, IEC 60529 IP66, IEC 62262 IK10 |

DORI (EN62676-4 standard)

| | | |
|----------------------------------|------|-----------------|
| Detect (25PPM/ 8PPF) | Wide | 37.5m(123.17ft) |
| Observe (63PPM/ 19PPF) | Wide | 15.0m(49.27ft) |
| Recognize (125PPM/ 38PPF) | Wide | 7.5m(24.63ft) |
| Identify (250PPM/ 76PPF) | Wide | 3.8m(12.32ft) |

QNO-7012R

4MP IR Bullet Camera



CAD

Unit: mm [inch]

