



Analog

Dome

SCD-3081

High Resolution WDR Varifocal Dome Camera



Key Features

- High resolution of 650TV lines, 700TV lines (B/W)
- Min. illumination 0.1Lux@F1.2 (Color), 0.01Lux (B/W)
- 3.9x V/F lens (2.8 ~ 11mm)
- 128x WDR
- VPS (Virtual Progressive Scan)
- intelligent Video
- True Day & Night (ICR)

SCD-3081

High Resolution WDR Varifocal Dome Camera



Specifications

Video	
Imaging Device	1/3" Super HAD CCD II (Double scan)
NETD	2 : 1 Interlace
Pixel Size	Color : 650TV lines, B/W : 700TV lines
Min. Illumination	0.1Lux@F1.2 (50IRE), 0.0002Lux (Sens-up, 512x)
Video Out	CVBS : 1.0 Vp-p / 75Ω composite
Lens	
Focal Length (Zoom Ratio)	2.8 ~ 11mm
Max. Aperture Ratio	1 : 1.2(Wide) ~ 2.8(Tele)
Angular Field of View	H : 94°(Wide) ~ 26°(Tele) / V : 67°(Wide) ~ 20°(Tele)
Min. Object Distance	0.2m (0.66ft)
Lens Type	DC auto iris
Pan / Tilt / Rotate	
Pan / Tilt / Rotate Range	0° ~ 352°
Tilt Range	0° ~ 73°
Operational	
Privacy Masking	Pelco-C (Coaxitron)
Gain Control	Fixed / Moved / Area / Fence / Tracking / Detection / Counting
White Balance	Off / On
LDC	Off / On
Environmental & Electrical	
Operating Temperature / Humidity	-10°C ~ +55°C (+14°F ~ +131°F)
Storage Temperature / Humidity	Less than 90% RH
Input Voltage	Dual (24V AC & 12V DC ± 10%)
Mechanical	
Color / Material	Ivory
RAL Code	Plastic (Dome cover : Clear)