



Analog

Dome

SCV-2120

12x High Resolution Vandal-Resistant Dome Camera



Key Features

- 1/4" Super HAD color CCD
- Based on W-V, the latest generation of Winner DSP engine
- Powerful 12x optical zoom (3.9 ~ 46mm) and 16x digital zoom
- SSNRIII, Upgraded 2D/3D noise reduction technology
- Day & Night with ICR (Infrared Cutfilter Removal)
- High resolution of 600TV lines (Color), 700TV lines (B/W)

SCV-2120

12x High Resolution Vandal-Resistant Dome Camera



Specifications

Video

Imaging Device	1/4" Super HAD CCD
NETD	2 : 1 Interlace
Pixel Size	Color : 600TV lines, B/W : 700TV lines
Min. Illumination	0.2Lux@F1.67 (50IRE), 0.0004Lux (Sens-up, 512x)
Video Out	CVBS : 1.0 Vp-p / 75Ω composite

Lens

Focal Length (Zoom Ratio)	3.9 ~ 46mm
Max. Aperture Ratio	1 : 1.67(Wide) ~ 1.88(Tele)
Angular Field of View	H : 51.54°(Wide) ~ 4.5°(Tele) / V : 39.24°(Wide) ~ 3.38°(Tele)
Min. Object Distance	1.8m (5.91ft)

Pan / Tilt / Rotate

Pan / Tilt / Rotate Range	0° ~ 340°
Tilt Range	0° ~ 146°

Operational

Motion Detection	Samsung-T/E, Pelco-D/P, Vicon, Honeywell, Panasonic, Bosch, AD
Privacy Masking	Pelco-C (Coaxitron)

Environmental & Electrical

Operating Temperature / Humidity	-10°C ~ +55°C (+14°F ~ +131°F)
Storage Temperature / Humidity	Less than 90% RH
Input Voltage	Dual (24V AC & 12V DC ±10%)

Mechanical

Color / Material	Ivory
RAL Code	Aluminum, Plastic (Dome cover : Clear)