



SPC-2001

Controller



Key Features

- Superior system compatibility by CMS (SSM, Wisenet Viewer) using PC
- 3D joystick control
- Quick and easy installation
- Hall-effect 3 Axis

※ Please refer to the Manual of the product to be connected for detailed functions

SPC-2001

Controller



Specifications

Communication		
Interface	4-pin USB Type A Port	
Operational		
Joystick	Hall-effect 3 Axis	
Button	12ea	
Performance		
Range of Movement	X/Y-Axis	-28° ~ +28°
	Z Axis	-23.5° ~ +23.5°
Center	Two Spring, Two Directions	
Minimum Power	0.109 [N · m]	
Operating Power	0.151 [N · m]	
Maximum Power	0.169 [N · m]	
Environmental		
Operating Temperature	0°C to +40°C (20% ~ 85% RH)	
Electrical		
Operating Voltage	(DC 5 [V]), Vdd = 5 [V] (±0.5 [V]) via USB	
Operating Current	50 [mA]	
Mechanical		
Dimensions (WxHxD)	182x182x106mm	
Weight	405g	
Materials		
Housing	ABS	
Handle	Poly Carbonate	
Cover	Rubber (Button)	
Shaft	SUM24L + Ni plating	
Cable Length	2 [m]	
Color	Black	

Software

Drivers	Standard DirectX Drivers (DirectInput)
----------------	--

SPC-2001

Controller



CAD

Unit: mm [inch]

