

## Housing & Mounts for PTZ Dome Camera (SPD-3750/3300/3000/2300/SNP-3300)



Mode	STH-330POV (Outdoor Housing)	STH-330PIV (Indoor Housing)	STH-320PO (Outdoor Housing)	STH-330PEV (Embedded Housing)	STB-270PWV (Wall Mounts)	STB-496PPV (Pendant Mounts)
Operating Temperature	-20°C ~ 50°C	-10°C ~ 50°C	-20°C ~ 50°C	-10°C ~ 50°C	-20°C ~ 50°C	-20°C ~ 50°C
Operating Humidity	0 to 90% RH	0 to 90% RH (non-condensing)	0 to 90% RH	0 to 90% RH (non-condensing)	0 to 90% RH (non-condensing)	0 to 90% RH (non-condensing)
Materials	Housing	ALDC 12	ALDC 10	EGI 1.2T	ALDC 12	ALDC 12
	Ring	ALDC 12	ALDC 12	ABS	EGI 1.2T	SPPS 32A / SCH 40
	Dome	Poly Carbonate	Poly Carbonate	-	-	SPCC
Antivibration / Waterproof	IP 67		IP 67	-	-	-
Dimensions	Ø242(W) x 284.5(H)mm Ø9.53" (W) x 11.2" (H)		Ø243(W) x 281(H)mm Ø9.57" (W) x 11.06" (H)	Ø235(W) x 188.5(H)mm Ø9.25" (W) x 7.42" (H)	270(W) x 175(H) x 140(D)mm 10.63" (W) x 6.89" (H) x 5.51" (D)	150(W) x 496(H)mm 5.91" (W) x 19.53" (H)
Weight	3.02Kg (6.66 lb)		1.55Kg (3.41 lb)	890g (1.96 lb)	1.2Kg (2.65 lb)	1.8Kg (3.97 lb)

### Dimensions

Unit : mm (inch)

