



Analog

UTP

SUD-3080

High Resolution WDR UTP Dome Camera



Key Features

- 1/3" Vertical double density color CCD
- Built-in SV-V, the latest generation of SV DSP engine
- Powerful dynamic range of 128x (NTSC), 160x (PAL)
- Built-in 3.9x (2.8 ~ 11mm) varifocal lens with auto iris
- SSNRIII, Upgraded 2D/3D noise reduction technology
- Day & Night with ICR (Infrared Cutfilter Removal)

SUD-3080

High Resolution WDR UTP Dome Camera



Specifications

Video	
Imaging Device	1/3" Sony Super HAD CCD II
NETD	2 : 1 Interlace
Pixel Size	Color : 600TV lines, B/W : 700TV lines
Min. Illumination	0.3Lux@F1.2 (50IRE), 0.0006Lux (Sens-up, 512x)
Video Out	CVBS : 1.0 Vp-p / 75Ω composite
Lens	
Focal Length (Zoom Ratio)	2.8 ~ 11mm
Max. Aperture Ratio	1 : 1.2(Wide) ~ 2.8(Tele)
Angular Field of View	H : 102°(Wide) ~ 28°(Tele) / V : 73°(Wide) ~ 21°(Tele)
Min. Object Distance	0.2m (0.66ft)
Lens Type	DC Auto Iris
Mount Type	Board-in type
Pan / Tilt / Rotate	
Pan / Tilt / Rotate Range	0° ~ 340°
Tilt Range	0° ~ 73°
Operational	
Motion Detection	Samsung-T/E, Pelco-D/P, Panasonic, Bosch, Honeywell, Vicon
Privacy Masking	Pelco-C (Coaxitron)
Gain Control	Fixed / Moved / Area / Fence / Tracking / Detection / Counting
White Balance	Off / On
LDC	Off / On
Environmental & Electrical	
Operating Temperature / Humidity	-10°C ~ +55°C (+14°F ~ +131°F)
Storage Temperature / Humidity	Less than 90% RH
Input Voltage	28V AC ±10%, 24V AC, 12V DC ±10%
Mechanical	
Color / Material	Ivory
RAL Code	Plastic (Dome cover : Clear)